



ISO 9001 : 2000 CERTIFIED CO.

# FLUID SEALING PRODUCTS

## NON ASBESTOS BRAIDED PACKINGS

INMARCO STYLE	DESCRIPTION	TEMP. °C	PH range	⊙		↔		⌞		SIZES
				P. bar	V.m/sec	P. bar	V.m/sec	P. bar	V.m/sec	
91	ULTRA PURE GRAPHITE FIBRE PACKING	- 250 TO + 650	0 - 14	100	30	50*	2	300	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
100	GRAPHITE FILAMENT YARN PACKING	- 200 TO + 600	0 - 14	125	20	150	2	400	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
100 FX	PREMIUM GRAPHITE PACKING WITH INBLEND GRAPHITED LUBRICANT	- 240 TO + 650	0 - 14	100	20	100	2	300	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
101	CARBON FILAMENT YARN PACKING	- 240 TO + 600	0 - 14	75	16	125	2	250	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
111	CARBON FIBRE PACKING WITH INBLEND GRAPHITED LUBRICANT	- 240 TO + 300	1 - 14	100	10	125	2	200	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
1081/ 108S	CARBON FIBRE PACKING WITH INCONNEL/STAINLESS STEEL WIRE	- 240 TO + 650	0 - 14	50	0.5	-	-	350	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
102	GORETEX EXPANDED P.T.F.E + GRAPHITE FIBRE PACKING	- 240 TO + 300	0 - 14	150	25	125	3	300	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
112	HYBRID FIBRE YARN OF EXPANDED P.T.F.E & GRAPHITE	- 240 TO + 280	0 - 14	125	25	100	2	250	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
103	GRAPHITE P.T.F.E. FIBRE PACKING	- 240 TO + 300	0 - 14	120	25	75	2	300	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
113	P.T.F.E. PACKING WITH INBLEND GRAPHITED	- 240 TO + 275	0 - 14	100	15	100	2	250	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
104	P.T.F.E. YARN PACKING WITH INLUBE SYNTHETIC LUBRICANT	- 240 TO + 260	0 - 14	75	10	100	2	225	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
104S	DRY P.T.F.E. FIBRE PACKING	- 240 TO + 260	0 - 14	50	5	100	1	150	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
104E	EXPANDED P.T.F.E. FIBRE PACKING WITH INLUBE SEALER	- 240 TO + 260	0 - 14	10	3	100	2	300	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
114 P/V	ECONOMICAL P.T.F.E. YARN PACKING FOR PUMPS & VALVES	- 200 TO + 260	0 - 14	50-P	4	100-P	1	200-V	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>

\*With INTHERM® Available On Request

# NON ASBESTOS BRAIDED PACKINGS

INMARCO STYLE	DESCRIPTION	TEMP. °C	PH range	⊙		↔		⚡		SIZES
				P. bar	V.m/sec	P. bar	V.m/sec	P. bar	V.m/sec	
 <b>105</b>	ARAMID FIBRE YARN PACKING WITH P.T.F.E FIBRE FACES	- 200 TO + 260	3 - 11	100	10	250	2	250	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>115</b>	CARBONACEOUS ARAMID YARN PACKING WITH P.T.F.E FIBRE FACES	- 240 TO + 275	2 - 12	125	12	275	2	300	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>106</b>	PURE ARAMID FIBRE YARN PACKING	- 240 TO + 260	3 - 11	75	10	200	2	200	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>116</b>	SPECIAL CARBONACEOUS ARAMID PACKING	- 240 TO + 275	3 - 12	100	12	250	2	300	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>107</b>	ARAMID YARN PACKING WITH EXPANDED P.T.F.E. + GRAPHITE FIBRE PACKING	- 240 TO + 275	2 - 12	100	22	500	2	250	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>117</b>	CARBONACEOUS ARAMID YARN PACKING WITH EXPANDED P.T.F.E. + GRAPHITE FIBRE PACKING	- 240 TO + 280	1 - 13	150	25	500	3	375	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>124/ 124T/ 124F</b>	GLASS FIBRE PACKINGS	- 240 TO + 540	0 - 14	100	5	25	0.5	150	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>124I/ 124IF</b>	GLASS FIBRE PACKING WITH INCONNEL WIRE	- 240 TO + 560	0 - 14	100	5	150	0.5	200	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>124 IG</b>	INCONNEL GLASS FIBRE PACKING	- 240 TO + 600	0 - 14	100	5	150	0.5	300	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>110</b>	BELGIAN FLAX FIBRE PACKING	Ambient TO + 100	5 - 10	25	7	50	1	150	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>120</b>	PREMIUM RAMIE FIBRE PACKING	- 40 TO + 150	6 - 11	50	10	100	2	200	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>125F/ 125T</b>	ACRYLIC YARN PACKING WITH INFLON P.T.F.E DISPERSION	Ambient TO + 150	4 - 10	50	7	125	1	150	-	3 mm <sup>2</sup> To 35 mm <sup>2</sup>
 <b>CART SEAL</b>	CUSTOM MADE CARTRIDGE OF VARIOUS SEALING MATERIALS	- 240 TO + 650	0 - 14	Upto 350	Upto 25	Upto 350	Upto 25	Upto 350	Upto 25	CUSTOM MADE
 <b>INSEAL COMP.</b>	BULK GLAND SEALING COMPOUNDS	- 200 TO + 300	0 - 14	50	20	100	2.5	200	-	STICKS IN 1 KG PACKS



ISO 9001 : 2000 CERTIFIED CO.

